



**LIGHT PROCESS COMPANY**

1631 Gillingham Lane  
Suite 100  
Sugar Land, Texas 77478

phone: 888-530-3600 ~ 281-530-3600


fax: 888-530-5195 ~ 281-530-5195

www.lightprocess.com

**LP11170**  
**NEW CONSTRUCTION**  
**NON IC**



**Housing** NON IC G24q-3 Base  
**Finish** 15 White  
**Lamp** One 26w HPF Electronic **Safe Thermally Protected UL Listed for Damp Location** All NON IC housings are not approved for use in Direct Contact with Insulation  
**Junction Box with Integral Romex Connector**  
Quick push and lock connector and branch through circuit wiring with 4 in, 4 out #12 wire, saves installation time  
**Breakaway Flange** Easy retrofit for use in existing ceilings and remodel applications  
**Housing Adjustment** Housing adjusts vertically for various ceiling thicknesses  
**Integral Captive Nail** Nails included for fast easy installation  
**Adjustable Socket Plate** Adjustable socket assembly provides flexibility in lamping options and precise lamp placement with various trims.  
**Bar Hanger** Bar hangers easily extend and will not fall out of plaster flange, providing sturdy installation.  
**Bar Hanger Locking Tabs** Squeeze tabs with pliers to lock bar hangers into place.  
 **One Class P HPF Electronic Ballast**  
**ENERGY STAR® Compliant**



**Trims Available:**



SEE TRIM PAGE FOR TRIM SPECIFICATIONS

All Products Shown Are U.L. Listed And Meet NEC When Housings And Trims Are Used As Specified

**LIGHT BULB DATA**

120V Compact Fluorescent

Catalog Number	Bulb Type	Base Type	Pin	Watts Rated	Rated Life (Hours)	Approx. Light (Lumen)	Approx. Color (Temp °K)	CRI
97045	Spiral	GX24q-3	4	26	10,000	1600	2,700	82
97046	Twin tube	GX24q-3	4	26	10,000	1600	2,700	82

fixture #      finish      lamp qty.      lamp watts      lamp code      options

LP11170 -      -

**PROJECT:** \_\_\_\_\_

**TYPE:** \_\_\_\_\_

LPC fixtures are UL listed and come with lamp and mounting hardware unless otherwise specified.